

IndraMotion for Packaging Automation system for the packaging industry



The market sets the pace

Staying close to the consumer, determining trends early on, and quickly incorporating findings into current products: Ever-shorter product lifecycles present great challenges for manufacturers of food, beverages, pharmaceuticals, and cosmetics. Consumer requirements change more quickly – global mega trends characterize consumer behaviour.

The demographic shift in industrial societies affects previous habits. More and more people are living in cities, households are becoming smaller, and the percentage of the elderly continues to rise. These trends increase the demand for smaller portion packs and food that can be prepared quickly. It therefore comes as no surprise that frozen foods and instant meals are taking up more space on supermarket shelves.

Consumers around the world are also more conscious about eating healthier and take the time to review ingredients as well as demand top quality. At the same time, more attention is being paid to specific brands, which must be renowned and clearly positioned to win over consumers and secure long-term success in regional and global markets.

Visual impressions also count, since attractive packaging arouses interest, lures customers, and increases recognition. New packaging and new packaging materials present products in a more captivating manner while fulfilling additional functions. Environment-friendly packaging made from recyclable materials, for example, is enjoying ever-increasing popularity.



IndraMotion for Packaging is a complete, intelligent solution for the food and packaging industry from Control City – your control technology capital.

www.control-city.com www.boschrexroth.de/packaging Such complex developments require new concepts from producers and machine manufacturers alike:

Ultra-fast flexibility for product changes

Automation enables changes to be made at the press of a button to ensure the feasibility of small batches, for example.

Modularity for high productivity

Modular machine concepts allow production lines to be quickly adapted for product changes, while the certified safety technology provides for high availability.

Ultra-high reliability for rapid processes

The quality of the integrated components plays a key role in realizing ever-increasing production speeds.

Standardization for easy-to-use

Intuitive user interfaces and standardized software tools simplify operation, even of complex plants, and shorten personnel training periods.

Energy efficiency and sustainability safeguard current and future success

Those who optimize energy consumption during development conserve the environment and save money in the long term.

Global partnership for reliability

International companies and globally-operating OEMs look for partners that offer products and services around the world.



IndraMotion for Packaging – the complete packaging solution

Rexroth has enjoyed success in the packaging industry for over 30 years. This experience has also been leveraged for IndraMotion for Packaging. Select all components for your customized automation concept using our modular system; perfectly coordinated control systems, HMI devices, and drives make automation all but child's play.

The requirements for packaging machines are more complex and differentiated than ever before and continue to place new demands on manufacturers. IndraMotion for Packaging is the ideal automation solution, regardless of whether pharmaceutical or food products in solid or liquid form are involved.

IndraMotion for Packaging bundles Rexroth's industry knowhow in a standardized complete solution for all segments of the food and packaging industry:

- food
- beverages
- confectionary
- pharmaceuticals
- cosmetics

Profit with all applications – from individual machines to entire production lines:

- form, fill and seal machines
- thermoforming machines
- bag machines
- Iabeling machines
- intelligent sorting systems
- casepacking machines
- cartoners
- pick-and-place robots
- ▶ palletizers







A competent partner, Rexroth offers end-to-end solutions tailored for the packaging industry. This also applies to all applications with motion control and PLC functionality – from operation and visualization through to drive system. We continually advance our systems to ensure that we meet your exact needs. The result of this development work is a very modular system, which integrates all components for flexible and intelligent automation – scalable, comprehensive, and open:

IndraWorks –

integrated engineering framework for configuring, programming, visualizing, and diagnosing all technologies

IndraMotion -

intelligent system software with integrated motion, robot, and logic control

IndraControl –

scalable control platform for HMI, operation, visualization, and I/O devices

IndraDrive –

intelligent drive solution with integrated motion logic, technology, and safety functions

Rexroth provides much more than just components, however. We can test and optimize your new ideas via simulation during the development phase. This minimizes expensive real-world testing and greatly reduces the time required to launch the product. Using proven tools for selecting optimum components helps in configuring an efficient machine from the very beginning. Expected power consumption can also be calculated, providing end customers peace of mind.









Benefits for the user

Future-proof system architecture

Maximum flexibility

Scalable control portfolio

- performance control platform: drive-, controller, and PC-based
- control system for motion, robotics, and logic

Ethernet-based system bus for

- ▶ motion
- drives
- ► I/O
- ► safety

Drive and control

- multi-technological integration (electricity, hydraulics, linear motion technology, pneumatics)
- mechatronic systems and modules
- cross-technology simulation



Sercos

the automation bus

Technology functions

- finished functions for all packaging processes
- parameterize instead of program
- ▶ 40 % less engineering time

Innovative cams

- quickest possible format and product changeovers
- flexible, segmented, and adaptive cams



Cam calculati



Robotics

- over 100 kinematic equations
- adaptive belt synchronization
- multi-kinematics
- integration of camera systems





Easy engineering

Low costs of ownership and best service

Decentralized drive technology

- ▶ 85 % lower costs for wiring
- 70 % lower control cabinet costs
- improved modularity of machines

"One-stop engineering"

- one engineering framework for all tasks
- multi-user engineering
- parameterize instead of program using technology functions

Open standards

- open interfaces
- sercos PackProfile
- programming according to IEC 61131-3 and PLCopen
- simple integration of 3rd-party solutions, e.g. sensors



98688

sercos

DeviceNet

омас



Energy efficient

Safety on Board

Energy System Design

raised operational safety

substantial less downtime

- Energy Efficient Components
- Energy on Demand
- Energy Recovery

Overall Equipment Efficiency

- up to 30 % higher line availability
- prevention of unplanned downtime
- preventative maintenance

World-wide support

- international project coordination
- global technical support and service
- large world-wide installed base

SAFETY ON BOARD







IndraWorks – rapid programming and easy operation

Today's modular machine concepts and increasingly complex tasks require a clearly-structured software architecture. Simple, complete solutions are what counts. Engineering and programming must be easy to realize, without any hassle, and it should be possible to operate the machine intuitively.

IndraMotion for Packaging helps you accommodate all engineering tasks centrally, in the IndraWorks engineering framework. This integrated framework guides you automatically through all steps – from project planning and programming to visualization and diagnosis on the machine. To this end, IndraWorks offers a wide range of features that facilitate cost-effective engineering:



Predefined project structure, interfaces, and state machines

Clearly-arranged, easy-to-use programs facilitate reusability

Open software architecture and object-oriented programming

For efficiently applying your machine know-how in the application program

Multi-user engineering

Simultaneously work with multiple users on a project

GAT – Generic Application Template

For rapid development of your application

Parameterize instead of program using technology functions

Prepared function blocks and automatic code generation free you of routine tasks

FDT/DTM technology

For seamless integration of 3rd-party components

Customer-friendly, cost-effective licensing model

Reasonable software costs for OEMs and machine users

Predefined technology functions considerably reduce engineering time by accelerating programming and facilitating reusability thanks to clearly defined structures and interfaces.

Examples of finished technology functions for packaging systems:

- intermittent duty of the machine cycle (No Product – No Bag, No Gap – No Seal)
- print mark control
- ► FlexProfile
- cams calculation
- magic belt
- measuring wheel
- ▶ probe
- flying shear
- product infeed
- product grouping
- cross sealing
- ► temperature control
- tension control
- and much more

IndraMotion for Packaging offers a wide range of advanced functions. End customers in packaging will see increased productivity:

- modular machine designs
- quick response to market and customer requirements as a result of easy modification
- simple operation of all processes from a standardized user interface

























Control technology from Rexroth – scalable, consistent, open

Rexroth controls communicate consistently with integrated, standardized interfaces and are based on open standards. Our competency allows us to offer upgradable complete solutions and customized service packages that utilize state-of-the-art technology and are very cost effective for successful automation.

IndraMotion MLC – scalable motion-logic system

- superior performance for synchronizing up to 64 drives per control system
- individual expansion using function modules for communication and technology
- direct connection for local inline I/Os, 8 high-speed I/Os already on board
- sercos, PROFIBUS, PROFINET IO, EtherNet/IP, Device-Net, Ethernet TCP/IP, and RS232 communication interfaces
- easy device exchange, since all data is on removable media
- future-proof thanks to extended hardware availability

IndraControl V – visualization devices and industrial PC

- controller-based compact operator panels measuring
 7.6 cm (3") to 26.4 cm (10.4") from the keypad unit to
 the touch screen
- embedded-PC-based terminals to 38.1 cm (15") touch screen
- embedded-PC-based manual operator panel for mobile use
- complete industrial PC portfolio from panel PC, to control cabinet PC with remote display, through to complete PC operating units

Flexible I/O systems with IP20 and IP67 protection

- ► I/O systems for centralized or decentralized connection
- ultra-fine channel selectivity of digital modules, with 2,
 4, 8, 16, or 32 channels
- comprehensive portfolio with digital, analog, function, relay, and feed terminals
- fieldbus coupler for sercos and all standard fieldbus systems
- ▶ IP67 version with M8 and M12 connection technology



Drive technology from Rexroth – intelligent and compact

The trend in packaging machine construction is toward greater flexibility and small, intelligent drives designed to handle specific tasks. In response, Rexroth has developed the revolutionary IndraDrive Mi and versatile Indra-Drive Cs to achieve further milestones in automating packaging machines.

IndraDrive Mi - the motor-integrated drive system

IndraDrive Mi combines drive electronics and a servo motor in an ultra-compact unit for substantially reduced overall size and cabling. This makes IndraDrive Mi the ideal solution for all applications for which only minimum space is available and ultra-high flexibility and maximum cost effectiveness are required.

- the ideal solution for modular machines
- ▶ up to 70 % reduction in control cabinet volume
- wiring costs reduced by up to 85 %
- all sizes covered, with IP65 protection, and for torques ranging from 2 to 30 Nm
- up to 20 drives on one daisy-chain cable
- absolute encoder and optional holding brake
- multiprotocol Ethernet for sercos, PROFINET IO, Ether-NET/IP and EtherCat
- multi-Ethernet interface to connect peripherals
- easy device exchange through removable media
- safety technology certified to EN 13849-1, Cat. 4 PLe and EN 62061 SIL 3

IndraDrive Cs - the compact series Multi-Ethernet drive

IndraDrive Cs can be used with many different communication configurations and encoders thanks to the new multiprotocol-capable communication hardware and multiple transducer interface. This makes it easier to choose the right device, reduces stock levels, and allows the IndraDrive Cs to cover wide range of applications in the lower power range.

- drastically reduced hardware variants
- extremely compact dimensions
- suitable for motors ranging from 0.05 to 9 kW of continuous power
- multiprotocol Ethernet for sercos, PROFINET IO, Ether-Net/IP, and EtherCat
- digital inputs/outputs and analog input integrated
- easy device exchange by way of intelligent operating panel with saving function for all data
- safety technology certified to EN 13849-1, Cat. 4 PLe and EN 62061 SIL 3





Better energy efficiency with Rexroth – less is more

Almost 70 % of industrial power consumption can be attributed to electrical drive systems. The potential for realizing savings is substantial; according to several studies, an average savings of 30 % can be achieved in this area, with up to 85 % possible.

In its 4EE concept, Rexroth has developed solutions aimed at reducing energy consumption in production processes and in plant and machinery – for all phases of the machine lifecycle: from development, to commissioning, through to modernization.



- Energy System Design
- Energy Efficient Components
- Energy on Demand
- Energy Recovery

Feasible measures and solutions from Rexroth	Savings potential*
Take the energy efficiency of the overall system into account in the design phase Mechatronic support/simulation	25 %
Optimal combination of mechanicals, transmission, motor, and drive control unit IndraSize design tool	20 %
Energy-optimized drive layout or motion design IndraSize, CamBuilder, FlexProfile	25 %
Best possible adaptation of the drive to the operating point Frequency/servo converter in place of power operation	25 %
Energy exchange between motorized and regenerative drives IndraDrive with DC bus	40 %
Feedback into the power line IndraDrive M/Mi with regenerative supply units	20 %
Electric buffering IndraDrive with additional DC bus capacitors for energy buffering during fast starts and stops	15 %
Standby concepts, intelligent load control/distribution, integrated energy monitoring Energy efficiency consultation provided by Rexroth	20 %

Overall Equipment Efficiency – reducing downtime

The competition among machine manufacturers and food producers continues to increase. It is in this context that Overall Equipment Efficiency (OEE) should be introduced, which quantifies the total efficiency of a machine or plant based on availability, output, and product quality:

OEE in % =	availability x	output x	product quality
Reduction for:	setupmachine failure	 material shortage brief interruptions lower production speed 	 rejects during start-up, product changeovers, and production
Examples	 product or format changeovers start-up times scheduled maintenance machine defect product or packaging rectification of faults removal of rejects machine not optimize unscheduled maintenance 		 damage caused to pro- ducts during production or packaging deficient packaging foreign particles in product

Using IndraMotion for Packaging allows you to better the overall efficiency of your machines and counteract increasing cost pressure. **Maximum production time** via the integrated and certified safety solution, Safety on Board, from Rexroth.



Ultra-fast product and format change-overs are possible, since FlexProfile from Rexroth knows the correlation of your machine's axes in detail and automatically takes this into account when format change-over required.

Highest quality all the time

Avoid unexpected failures by permanently monitoring critical parameters using the Rexroth Productivity Agent for predective maintenance of your machines.

Technical data

System software		IndraMotion MLC			IndraMotion MLP
Hardwa	are variant: IndraControl	L25 ¹⁾	L45 ¹⁾	L65 ¹⁾	VEP ²⁾
1	Axes				
1.1	Number of axes per control system (real, virtual, encoder, group)	16	32	64	32
1.2	Max. number of axes in control group (C2C)	1,024	2,048	4,096	2,048
2	On board interfaces				
2.1	sercos III	•	•	•	•
2.2	Ethernet TCP/IP	٠	٠	•	•
2.3	Real-Time Ethernet: PROFINET RT, EtherNet/IP	-	•/•	●/●	●/●
2.4	PROFIBUS-V1 master/slave	-	•/•	•/•	●/▼
2.5	Digital inputs/outputs (50 µs, interrupt-enabled/500 µs)	-	8/8	8/8	-
3	Function modules (optional)				
3.1	Max. number of function modules per control system	2	4	4	_
3.2	sercos III cross communication (C2C)	•	•	•	-
3.3	PROFIBUS master	-	٠	•	-
3.4	Realtime Ethernet: PROFINET RT, EtherNet/IP and PROFIBUS	•	•	•	_
3.5	Realtime Ethernet: PROFINET RT, EtherNet/IP and DeviceNet	•	•	•	-
3.6	DeviceNet master	•	٠	•	-
3.7	FAST I/O: 8 inputs (typ. deceleration time of 40 μs), 8 inputs/outputs, 8 outputs (typ. deceleration time of 70 μs)	•	•	•	-
3.8	High-speed programmable limit switches (125 µs, 16 outputs)	•	٠	•	_
4	I/O modules, bus couplers				
4.1	Inline: digital, analog, relays, technology (local at the control system)	•	•	•	_
4.2	sercos III block I/O (digital/analog)	•	•	•	•
4.3	sercos III bus coupler for inline I/Os	•	•	•	•
4.4	PROFIBUS bus coupler for inline I/Os	●3)	•	•	•
4.5	IndraContol S67/Fieldline (IP67)	●3)	٠	•	•
5	Drives supported				
5.1	IndraDrive M, C, Mi, Cs	•	•	•	•
5.2	3rd-party via sercos PackProfile	•	•	•	•
6	HMI connection				
6.1	IndraControl VEP embedded-PC	•	•	•	•
6.2	IndraControl VCP compact operator units	•	•	•	-
6.3	Industrial PC IndraControl VPP, VSP, VPB, VSB	•	•	•	-
7	Service, maintenance				
7.1	Remote access via service tool	•	•	•	•
7.2	PC-free component exchange	•	•	•	-

¹⁾ Controller-based control hardware ● Standard ▼ In preparation ³⁾ With real-time Ethernet function module and PROFIBUS

14

System	a software		IndraMotion MLC		IndraMotion MLP	
Hardwa	are variant: IndraControl	L25 ¹⁾	L45 ¹⁾	L65 ¹⁾	VEP ²⁾	
8	Engineering framework IndraWorks					
8.1	Programming languages according to IEC 61131-3	IL, ST, FBD, LD, SFC, CFC				
8.2	Project management	٠	•	•	•	
8.3	Version management/multi-user interface	•	•	•	•	
8.4	System configurator, library administration	•	•	•	•	
8.5	Fieldbus and I/O configurator	•	•	•	•	
8.6	Online/offline switching	•	•	•	•	
8.7	Commissioning assistants	•	•	•	•	
8.8	Debugging and diagnostics	•	•	•	•	
8.9	Firmware administration	•	•	•	•	
8.10	HMI engineering (interfaces)	•	•	•	•	
8.11	Cam editor	•	•	•	٠	
8.12	FlexProfile configurator	•	•	•	•	
9	Technology functions (selection)					
9.1	Jog functions, cross sealer, perforation feeder, cams calculation, FlexProf toggle lever kinematics, tension control, probe, temperature controller, w	file, inline machinin inder, productivity	g, intermittent duty agent, and much m	, product infeed, proo	duct grouping, crank and	
10	Logic control					
10.1	IndraLogic PLC kernel according to IEC 61131-3	•	•	•	•	
10.2	Freely configurable tasks (cyclical, free-running, event-controlled)	8	8	8	8	
10.3	External event tasks, sercos synchrony/system-specific	1/1	1/1	1/1	1/1	
10.4	Minimum cycle time (sercos/motion)	1/2 ms	1/1 ms	0.25/1 ms	1/1 ms	
11	Motion control					
11.1	Single axis (torque, speed, position)	•	•	•	•	
11.2	Electronic synchronization (angle, speed)	٠	•	•	•	
11.3	Cams in drive (max. 1,024 sort points)			1 per drive		
11.4	Cams in the control system			99		
11.5	Points table for cam	•	•	•	•	
11.6	Segmented cam profile (up to 16 segments)	•	•	•	•	
11.7	FlexProfile	•	•	•	•	
11.8	Virtual/real masters	•	•	•	•	
12	Integrated motion laws (selection)					
12.1	User-specific cam; 5th-order polynomial, 7th-order polynomial; linear mot and much more	ion, sines, modifiec	acceleration trape	zoidal, speed-limited	and jerk-limited motion,	
13	Robot control					
13.1	Max. number of kinematic equations (= robots) per control system	16	16	16	-	
13.2	Max. number of axes per kinematic chain (incl. belt axes)	16	16	16	-	
13.3	Max. number of belts per control system/kinematic equation	16/4	16/4	16/4	-	
13.4	Linear/circular interpolation (also belt synchrony)	•	•	•	-	
13.5	Point-to-point (also belt synchrony)	•	•	•	-	
13.6	Work area monitoring (software limit switch)	•	•	•	-	
13.7	Speed/acceleration control (path and axis)	•	•	•	-	
13.8	Override for speed/acceleration/deceleration	•	•	•	-	
13.9	Belt synchronization (continuous or intermittent belts)	•	•	•	_	
13.10	Movements with blendings (also from and to a belt-synchrony point)	•	•	•	_	
13.11	Exact-position switching with lead time	•	•	•		
13.12	Teach-in function/jogging (jogging of axes)	•	•	•		
13.13	Axis/machine/product coordinate system	•	•	•	-	

¹⁾ Controller-based control hardware ● Standard ▼ In preparation ²⁾ Embedded-PC-based control hardwareNot available

³⁾ With Real-Time Ethernet function module and PROFIBUS



Bosch Rexroth AG

Electric Drives and Controls P.O. Box 13 57 97803 Lohr, Germany Bgm.-Dr.-Nebel-Str. 2 97816 Lohr, Germany Phone +49 9352-40-0 Fax +49 9352-40-4885 www.boschrexroth.com/electrics

71 245 AE/2011-06-A4-SM R911318188 © Bosch Rexroth AG 2011 Subject to revisions! Printed in Germany The data specified above only serve to describe the product. As our products are constantly being further developed, no statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging.