

Control units

# Single-axis BASIC PROFIBUS



Control units

**Single-axis ■ BASIC PROFIBUS**

The PROFIBUS field bus interface has been used successfully for many years in automated manufacturing technology and process automation. This bus system is the means by which the control system cyclically exchanges with the bus users all the specified and actual values, including status and diagnostic messages. The correct interface for connecting the IndraDyn motors or other standardized encoders, such as Hiperface®

, is already integrated.

Start-up with the IndraWorks engineering framework is a convenient option via PROFIBUS.

**Technical data**

IndraDrive control units		
Master communication		
PROFIBUS		●
Configurations		
Option 1	Encoder interface	●
Safety option		●
Encoder interfaces		
IndraDyn motors MSK, MKE, MAD and MAF, Hiperface®, 1 Vpp and 5 V TTL		●
Safety options compliant with EN 13849-1 und EN 62061		
Safe Torque Off (Cat. 3 PL e/SIL 3)		○
Control panel		
Standard		●
Cycle times		
Current control	[ $\mu$ s]	125
Velocity control	[ $\mu$ s]	250
Position control	[ $\mu$ s]	500
PWM frequency		
4 kHz		●
Inputs/outputs		
Digital inputs		5
Digital inputs utilizable for touch probes		1
Digital inputs/outputs (any adjustments)		3
Relay outputs		1

Control units

**Single-axis ■ BASIC PROFIBUS**

---

Interfaces		
RS232		●
Control voltage data		
Control voltage		24 V DC
Power consumption without options	[W]	7.5

- Basic configuration
- Optional

**Bosch Rexroth AG**

Postfach 13 57  
97803 Lohr, Germany  
Bgm.-Dr.-Nebel-Str. 2  
97816 Lohr, Germany  
Tel. +49 9352 18-0  
Fax +49 9352 18-8400  
[www.boschrexroth.com/electrics](http://www.boschrexroth.com/electrics)

**Local contact information can be found at:**

[www.boschrexroth.com/adressen](http://www.boschrexroth.com/adressen)

The data specified above only serve to describe the product. As our products are constantly being further developed, no statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification.

It must be remembered that our products are subject to a natural process of wear and aging.